



Active System Integration

FBAC603 - Standalone Fingerprint Time and attendance CumAccess control

Product Description

FBAC 603(702S) is a standalone fingerprint T&A + Access Control system, IN and OUT status, also low price with good performance, designed especially in the purpose of popularizing the fingerprint products.

It could store 2,200 fingerprint templates and 50,000 transaction records.

It will bring you much profits because of its low price.



Technical Specification

- Dimension(WxHxD): 140.5 X 116 X 43.5 mm
- User Capacity:2,200
- Transaction Storage :50,000
- Communications: RS232 ,RS485, TCP/IP ,USB (optional)
- Identification time : < =2S
- FAR: <=0.0001%
- FRR: <=1% Operating
- Temperature : 0°C - 45°C
- Operating Humidity : 20%-80%
- Sensor: OEM Optical Sensor 500 DPI
- Card reader: EM RFID(Proximity), Mifare(optional) ,HID (optional)
- Access Control Interface: 3rd party electric lock
- door sensor, exit button, alarm, Door Bell
- Power Supply: 12V DC
- Standard Function: Work code ,DLST ,Anti-Pass Back
- Optional Function:Schedule-Bell ,9 Digit User ID
- Wigand Signal: Input & Output
- Alogrithm Version: Finger v9.0
- Dispaly: Black & White LCD Screen
- Gross Weight: 0.85 Kg
- Language: English