



F 707

➔ Standalone TFT - Fingerprint Time & Attendance and Access Control Terminal

Users : 2,200 Fingerprints

Transaction Storage : 50,000 Logs

Sensor : Optical Sensor

Communications : RS232 , RS485 , TCP/IP

Identification time : ≤ 2 sec

FAR : $\leq 0.0001\%$

FRR $\leq 1\%$

Wiegand Signal : Output

Access Control Interface : 3rd party electric lock ,
door sensor , exit button , alarm . door bell

Algorithm : 9.0 Version

Operating Temperature : $0^{\circ}\text{C} - 45^{\circ}\text{C}$

Operating Humidity : 20% - 80%

Power Supply : 12V DC

Display : B&W LCD Screen

Dimension(WxHxD) : 90 x 190 x 39.5 mm

Gross Weight : 0.7 kg

Standard Functions : SMS , DLST

Optional Functions : Webserver, Workcode, 9 digit user ID
Self Service Query , Automatic Status Switch , Printer

Features:

Fingerprint reader with durable and highly accurate optical sensor.

1-touch 1-second employee recognition.

No need to enter PINS.

Supports 50 time zones , 5 groups and 10 unlock combinations.

Tamper-proof switch and alarm outputs.

Request-to-exit and alarm contacts.

Operates stand-alone without a computer.