

Full HD in CCTV

3 Megapixel Network Camera



3Megapixel Full HD Network Vandal-Resistant Dome Camera

SNV-7080

The SNV-7080 is an ONVIF compliant 3 Megapixel vandal dome camera that incorporates Samsung's WiseNet2 DSP chipset. This camera is capable of displaying multiple resolutions from CIF (320 x 240) through to 16:9 format 1080p full HD and up to 3 megapixel (2048 x 1536). The SNV-7080 provides up to 10 video streams and offers both H.264 & MJPEG. The SNV-7080 Series cameras feature Smart Compression where a predefined Region of Interest (ROI) or faces (Face detection) are compressed differently than the rest of the image making them clearer while maximizing bandwidth and storage efficiency.

- Max. 3M (2048 x 1536) resolution
- 16:9 Full HD (1080p) resolution support
- 3~8.5mm (2.8x) motorized varifocal lens
- H.264 / MJPEG multiple codecs
- WDR (supported in 2M mode only)
- Smart Compression (ROI encoding)
- True Day/Night (ICR)
- POE or 24VAC
- IP66



3Megapixel Full HD Network Vandal-Resistant Dome Camera

SNV-7080




ONVIF



Dimensions

Unit : mm (inch)



Accessories (Optional)



Specifications

SNV-7080N/P

VIDEO	
Imaging Device	1/2.8" 3M PS CMOS
Total Pixels	2,144(H) x 1,588(V)
Effective Pixels	2,096(H) x 1,561(V)
Scanning System	Progressive
Min. Illumination (TBD)	Color : 1Lux (F1.2, 50IRE), 0.017Lux (Sens-up 60x) B/W : 0.08Lux (F1.2, 50IRE), 0.001Lux (Sens-up 60x)
S / N Ratio	50dB
Video Output	CVBS : 1.0 Vp-p / 75Ω composite, 704 x 480(N), 704 x 576(P), for installation
LENS	
Focal Length (Zoom Ratio)	3 ~ 8.5mm (2.8x) Motorized vari-focal
Max. Aperture Ratio	F1.2
Angular Field of View	H : 100°(Wide) ~ 35.3°(Tele), V : 74.6°(Wide) ~ 26°(Tele)
Min. Object Distance	0.5m (1.64ft)
Focus Control	Remote control via network (Manual, One-shot AF)
Lens Type	DC auto iris
Mount Type	Board-in type
PAN / TILT / ROTATE	
Pan Range	0° ~ 355°
Tilt Range	0° ~ 90°
Rotate Range	0° ~ 355°
OPERATIONAL	
Camera Title	Off / On (Displayed up to 15 characters)
Day & Night	Auto (ICR) / Color / B/W / External B/W
Backlight Compensation	Off / BLC / HLC / WDR
Wide Dynamic Range	(* 2M mode only), 52dB
Contrast Enhancement	SSDR (Samsung Super Dynamic Range) (Off / On)
Digital Noise Reduction	SSNRIII (2D+3D noise filter) (Off / On)
Motion Detection	Off / On (4 programmable zones)
Privacy Masking	Off / On (1ea 4 point polygonal + 16ea rectangular zones)
Sens-up (Frame Integration)	Off / Auto (2x ~ 60x)
Gain Control	Off / Low / Medium / High
White Balance	ATW / AWB / Manual / Indoor / Outdoor
Electronic Shutter Speed	Auto / A.FLK / Manual (1/30 ~ 30,000sec)
Flip / Mirror	Off / On
Alarm I/O	Input 1ea / Output 1ea (Relay)
NETWORK	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.264, MJPEG
Resolution	3M mode - H.264 : Max. 20fps at all resolutions
	MJPEG : 800 x 600 ~ 320 x 180 - 20fps
	1280 x 1024 ~ 1600 x 1200 - 15fps
	1920 x 1080 ~ 2048 x 1536 - 10fps
2M mode - H.264 : Max. 30fps at all resolutions (When WDR on, Max. framerate is Max. 15fps.)	
MJPEG : 800 x 600 ~ 320 x 180 - 30fps	
1280 x 1024 ~ 1920 x 1080 : 15fps	
Max. Framerate	3M mode : Max. 20fps, 2M mode : Max. 30fps * When WDR on, Max. framerate is Max. 15fps
Smart Codec	Yes (Area based method, Face detection method)
Video Quality Adjustment	H.264 : Compression level, Target bitrate level control MJPEG : Quality level control
Bitrate Control Method	H.264 : CBR or VBR, MJPEG : VBR
Streaming Capability	Multiple streaming (Up to 6 profiles)
Audio I/O	Mic / Line in, Line out
Audio Compression Format	G.711 u-law
Audio Communication	Bi-directional audio
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, ONVIF
Security	HTTPS(SSL) login authentication, Digest login authentication IP address filtering, User access log, 802.1x authentication
Streaming Method	Unicast / Multicast
Max. User Access	10 users at unicast mode
Memory Slot	SD/SDHC memory slot
ONVIF Conformance	Yes
Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatian, Hungarian, Greek
Web Viewer	Supported OS : Windows XP / VISTA / 7, MAC OS Supported Browser : Internet Explorer 7.0 or Higher, Firefox, Google Chrome, Apple Safari
Central Management Software	NET-i viewer
ENVIRONMENTAL	
Operating Temperature / Humidity	-40°C ~ +50°C (-40°F ~ +122°F) / Less than 90% RH
Ingress Protection	IP66 Grade (Waterproof)
ELECTRICAL	
Input Voltage	12V DC, 24V AC, PoE (IEEE802.3af)
Power Consumption	Max. 7W (Heater off), Max. 11W (Heater on) *Heaters work with 24VAC only
MECHANICAL	
Color / Material	Ivory / Aluminum
Dimensions (WxH)	Ø160.0 x 134.5mm (Ø6.3" x 5.3")
Weight	1.4Kg (3.09 lb)

DISTRIBUTED BY



SAMSUNG TECHWIN AMERICA Inc.
100 Challenger Road, Suite 700, Ridgeland Park, NJ 07660, UNITED STATES
Toll Free : 1-877-213-1222 Fax : 1-201-373-0124
www.samsungsecurityusa.com



The Eco mark represents
Samsung Techwin's will to create
environment-friendly products, and indicates
that the product satisfies the EU RoHS Directive.

Design and specifications are subject to change without notice.

www.asi.ind.in

I.E-1103