

CP- UNC-T4352L3

3 MP HD IP IR Bullet Camera

CP PLUS
APEX series



Main Features

- 1/3" 3 MP Progressive Scan CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 20fps@3M(2048×1536), 25/30fps@1080P
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- 6mm fixed lens (3.6mm,8mm optional)
- IR Range of 30 Mtrs.
- Supports PoE, IP66
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-T4352L3

3 MP HD IP IR Bullet Camera

CP PLUS
APEX series

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Gain Control(AGC)
 Lens
 Video Compression
 Back Light Compensation
 S/N Ratio
 Video Streaming
 Resolution
 Privacy Mask
 ICR

Specification

1/3" 2 Megapixel CMOS
 0.01 Lux@F1.2, 0Lux/F1.2(IR on)
 Auto/Manual, 1/3~1/10000s
 Auto/Manual
 Auto/Manual
 6mm (3.6mm,8mm optional)
 H.264/MJPEG
 BLC / HLC / DWDR
 More than 50 dB
 Main Stream:1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
 3.0M(2048 x 1536) /1080P(1920 x 1080) / 720P(1280 x 720) /D1(704 x 576) / CIF(352 x 288)
 Up to 4 areas
 Auto(ICR)/Color/B/W

Protocol
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S

Ethernet
 RJ-45 (10/100Base-T)

User Account
 20 users

IR
 IR Range of 30 Mtrs.

Smart Phone
 iPhone, iPad, Android, Windows Phone

Operating Temperature
 -20°C~+60°C, Less than 95% RH

Power Source
 DC12V, PoE(802.3af)

Power Consumption
 <5W

Weatherproof Standard
 IP66

Regulatory
 CE, FCC and RoHS

Dimension
 70mm×66mm×160mm

Weight
 0.5kg