-7-inch color intelligent extension station

Touch- Future -Perfect integration of technology and furnishing art

VTH15 Series is a full touch control indoor intelligent terminal. 7-inch color high definition screen presents you the colorful video. The touch panels with the control button realize the fluent operation. The comfortable life, the hear beats with the finger. It supports cable or wireless alarm function and can connect to the alarm detectors such as the gas leak detector, intruder detector, smoke detector and etc, which creates safe living environments for you. It can connect to the USB camera to realize the remote video talk and make there is no distance between you and me.





-Features

Displayer: Color 7-inch TFT LCD, resolution 800*480 Protocol: TCP/IP OS: Embedded Linux Video format: H.264 Extension port : 2 USB 2.0 ports Network port: 1 10M/100Mbps self-adapter Ethernet port Dimensions: 220mm *153mm * 23mm (W*H*T) Power: DC 10~15V Power consumption: Standby≤1w, work≤7w

Video door phone

Realize the hand free video door phone with the public door station, unit door station

Send or receive the call from the management center device

Extension USB camera realize video door phone with other resident in the same community

Open unit door lock Set disturbance free mode

Security function:

Visitor recognition and open the unit lock Extend to connect to the eight cable alarm zones or eight wireless alarm zones Storage 10 residents' video or message, 30 visitor video, 1000 visitor picture Emergency button to call the management centre

Control function (Via wireless module):

Temperature control Light and curtain control Scene mode control

General management

Community bulletin Message prompt Elevator call

Data sheet

ltem	DH-VTH1500A	DH-VTH1510A	DH-VTH1550A		
System		•			
General	Embedded Processor				
Processor					
Operating	Embedded LINUX				
System					
Video					
Video	H.264				
Compression					
Audio					
Input	Omnidirectional microphone				
Output	Embedded loudspeaker				

Intercommunicati on						
on	Support bidirectional communication					
Display						
Screen	7 inch TFT color LCD					
Resolution	800*480					
OSD Menu	Chinese/ English					
Operate Mode						
Input	Mechanical button	screen/Mechanical	Touch screen/ Touch Button			
Alarm						
Input(extend available)	Wire:6	Wire:6 Wireless: 16	Wire:6 Wireless:			
	16					
Output Network						
Network Ethernet	10N//100N/hpg colf adapting					
	10M/100Mbps self-adapting					
Network protocol TCP/IP, SNMP Storage						
	Maximum 16GB TF card					
Memory	128MB					
Hardware interface						
USB	N/A	1	1			
Environment						
Power Supply	DC 10~15V					
Power Consumption	Standby ≤1w,Working≤7w					
Dimension	220mm *153mm * 23mm(W*D*H)					
Weight	600g					